

Compact Commercial Softeners

CC206c, CC208c

High performance systems for applications where space is critical. Efficient and user-friendly softener range.








The CC series comprises best-in-class, compact commercial softeners that are incredibly quick and easy to install.

- Compact and durable design, available on casters.
- Uses a process of counter-current regeneration.
- Highly efficient commercial water softener that regenerates only on demand.

Specifications

Product Name	CC 206c	CC 208c
Width	356 mm	508 mm
Depth	356 mm	559 mm
Height	559 mm	711 mm
Weight	27,2 - 49,9 kg	45 - 100 kg
Performance		
Minimum Flow	1,1 l/min	1,1 l/min
Maximum Flow @ 1 Δ bar	34,5 l/min	38,6 l/min
Hardness as CaCO₃ (max)	513 mg/l	684 mg/l
Regeneration		
Salt Used / Capacity	0,23 - 0,45 / 18 kg	0,45 - 0,64 / 45 kg
Time	11 minutes	11 minutes
Volume	19 litres	53 litres
System		
Media Volume	2 x 4,5 litres	2 x 11 litres
Inlet/Outlet Connections	Custom	Custom
Maximum Temperature	65°C	65°C
Inlet Pressure (min/max)	1,0 / 8,6 bar	1,0 / 8,6 bar

Features:

-  Fits Under Kitchen Cabinet
-  Quick Connect/ Easy Install
-  High Temperature
-  Non-electric
-  On Casters/ Moveable

Why Kineticico CC Series?

Kineticico's patented Mach series control valve eliminates the need to adjust, set, repair and replace timers, computers or electrical components.

The Kineticico control valve simultaneously manages two media tanks through service and regeneration cycles. Water pressure runs the system, measuring the amount of water processed and regenerating on demand.

Since the system is comprised of two media tanks, soft water is used for the complete regeneration process, which substantially improves product lifetime, efficiency and water quality.